

IMP+

Self-contained ultrasonic level measurement without compromise.

The IMP series is a range of compact, low-profile self-contained units with the benefit of digital echo processing.

There is an IMP unit to suit your application. 3 m (9 ft), 6 m (19 ft), and 10 m (32 ft) range versions are available and each can be wired for 2 wire or 3 wire operation. The IMP+ features an LCD display and digital temperature measurement and compensation with 2 relay outputs as standard.

Where Can I Use the IMP+?

The IMP+ can be used wherever you need a reliable non-contacting level measurement: digital echo processing means IMP+ is perfect for solids or liquids. Sumps, tanks, silos. Anywhere you need a display telling you the level or an analog output to interface with your site control system or drive a display.

Battery Power

When used on battery power for intermittent (wake-up) applications, the IMP+ features a high-speed boot up of around circa 3 seconds which maximizes battery life. For example, if an IMP were switched on every 15 minutes for a 3-second reading, the average current is a mere 40 μ A.

System Integration

Active and passive (sourcing and sinking) analog outputs assist with system integration, especially when retrofitting into older installations.



THE RIGHT METER FOR

- Tank Level Applications
- Chemical Dosing
- Simple Level Indication
- Open & Closed Vessel Level Requirements
- Solids Level Indication

Simple to Install


The compact IMP+ is only 175 mm (6 in) high with a 5 in (130 mm) diameter. Cable glands are provided and IMP+ can be simply screwed into a 1.5" or 2" universal fitting (a 1.5" or 2" adapter is available). High transducer power and tight beam angles, together with Pulsar Measurement's digital echo processing, makes IMP+ ideal for many "difficult" applications such as dusty or foamy environments, or where a tank has unavoidable intrusions.

The integral display makes programming IMP+ extremely straightforward. IMP+ can be completely set up, without compromising the IP rating, using the integral keypad alone with no need for a PC. Optional IMP PC software makes it easy to fine-tune IMP's performance and "clone" any number of IMP units to the same settings if, for example, they are being used on a tank farm.

IMP+ PC Software

IMP PC is optional software that extends the capabilities of the IMP+ and allows a user to:

- **Download, analyze, and store echo profiles.** A great way to see exactly what is happening in the application. Fine-tuning for ultimate performance.
- **Set-up IMP+.** All programming parameters are instantly visible in the IMP PC programming screens. Program the IMP unit on a desktop before installation, or clone several IMPs to save valuable time.
- **Updates.** Future-proof your IMP+! Pulsar Measurement's policy of continual improvement means that we never stop developing our products. IMP PC allows new firmware to be installed into your IMP units, without even removing them from the application.
- **Flow Measurement.** A flow curve may be added within IMP PC to configure for simple level to flow linearization.



Inside of an IMP+



Optional IMP mounting bracket.

Service & Installation

Our award-winning products are favored worldwide due to their reliability and easy menu-driven set-up.

All products from Pulsar Measurement are designed to be easily installed and set up, but if you are unsure of your installation, our service engineers are ready to assist you. From telephone and web support to onsite commissioning and on/off-site product training, we will ensure that you get the most out of your product and sales experience with Pulsar Measurement.

If you are unsure of your application requirements or which product is right for you, our technical teams can advise you on the best solution to your application and technology requirements, making sure that you get the most accurate and reliable readings every time.

For more information on our service offerings, please visit the website or contact one of our head offices.

Technical Specifications

PHYSICAL

Controller Body Dimensions:	186 mm H x 133 mm D (5.24 in x 7.32 in)
Weight:	Nominal 1 kg (2.2 lb)
Cable Entry Detail:	2 off cable glands 4.5 mm to 10 mm (Torque to 2Nm)
Mounting:	1.5 in BSP/NPT (IMP3 & IMP6), 2 in BSP/NPT (IMP10)

ENVIRONMENTAL

IP Rating:	IP67
Temp. Range (Process):	-40 °C to +80 °C (-40 °F to +176 °F)
Temp. Range (Ambient):	-20 °C to +65 °C (-4 °F to +149 °F)

IMP3

Beam Angle (-3dB Half Power):	<10° inclusive
Operating Frequency:	125 kHz
Measurement Range:	0.2 m to 3 m (0.66 ft to 10 ft)

IMP6

Beam Angle (-3dB Half Power):	<10° inclusive
Operating Frequency:	75 kHz
Measurement Range:	0.3 m to 6 m (0.98 ft to 20 ft)

IMP10

Beam Angle (-3dB Half Power):	<10° inclusive
Operating Frequency:	41 kHz
Measurement Range:	0.3 m to 10 m (0.98 ft to 33 ft)

APPROVALS

CE Approval:	Listed in the Certificate of Conformity within the manual
---------------------	---

PERFORMANCE


Input Voltage:	11-30 V, 3.5-22mA
Accuracy:	±0.25% or 6 mm (0.24 in), whichever is greater
Resolution:	± 0.1% or 2 mm (0.08 in), whichever is greater
4-20mA Outputs:	Resolution 5 µA, both active and passive outputs
Temperature Compensation:	Via internal temperature sensor (±0.5 °C (32.9 °F) accuracy). Level and volume conversion are installed allowing linearization for tank shapes
PC Interface-PC Suite:	All parameters can be accessed and changed through PC Suite software. Echo traces may be viewed on screen.

2 WIRE CONFIGURATION FEATURES


- RS232 (RJ11 port) connection for diagnostics and software updates
- 4 Digit LCD display
- 4 button keypad for parameter entry
- Power consumption: 3.5-22mA
- Passive 4-20mA output

3 WIRE CONFIGURATION FEATURES

- All 2-wire version features plus:
- Backlit LCD display
- 0-10 V analog output
- 2 relays: single pole two way, 1A 30 V DC/AC
- Power consumption with relays energised <60mA (less 12mA/relay not energized)
- Active and passive 4-20mA outputs



IMP drawing side



IMP drawing top

Delivering the Measure of Possibility

Pulsar Measurement offers worldwide professional support for all of our products, and our network of reps and distributors all offer full support and training. Our facilities in Malvern, UK and Largo, USA are home to technical support teams who are always available to answer your call or attend your site when required. Our global presence, with direct offices in the UK, USA, Canada, and Malaysia allow us to create close relationships with our customers and provide service, support, training, and information throughout the lifetime of your product.

For more information, please visit our website:

www.pulsarmeasurement.com



INFO@PULSARMEASUREMENT.COM

Pulsar Measurement is a trading name of Pulsar Process Measurement, Ltd.

*Copyright © 2020 Pulsar Measurement
Registered Address: 1 Chamberlain Square CS, Birmingham B3 3AX
Registered No.: 3345604 England & Wales*

Delivering the Measure of Possibility

United States

11451 Belcher Road South
Largo, FL 33773

888-473-9546

Canada

16456 Sixsmith Drive
Long Sault, Ont. K0C 1P0

855-300-9151

United Kingdom

Cardinal Building, Enigma
Commercial Centre
Sandy's Road, Malvern WR14 1JJ

+44 (0) 1684 891371

Rev 1.0